



- 3,5-DIGIT PROGRAMMABLE PROJECTION
- MULTIFUNCTION INPUT UNI (DC, PM, RTD, T/C, DU)
- DIGITAL FILTERS, LINEARIZATION
- SIZE OF DIN 96 X 48 MM
- POWER SUPPLY 80...250 V AC/DC
- Option
 - Excitation • Comparators • Data output • Analog output
 - Power supply 10...30 V AC/DC • Three-color display - 20 mm

OPERATION

The instrument is set and controlled by five control keys located on the front panel. All programmable settings of the instrument may be performed in three adjusting modes:

LIGHT MENU is protected by optional number code and contains solely items necessary for instrument setting

PROFI MENU is protected by optional number code and contains complete instrument setting

USER MENU may contain arbitrary items from the programming menu (LIGHT/PROFI), which determine the right (see, change). Access w/o password.

Standard equipment is the OM Link interface, which together with operation program enables modification and filing of all instrument settings as well as perform firmware updates (with OML cable). The program is also designed for visualization and filing of measured values from more instruments

All settings are stored in the EEPROM memory (they hold even after the instrument is switched off).

OPTION

EXCITATION is suitable for feeding of sensors and transmitters. It is isolated, with continuously adjustable value in the range of 5...24 VDC.

COMPARATORS are assigned to monitor two limit values with relay output. The limits have adjustable hysteresis within the full range of the display as well as selectable delay of the switch-on in the range of 0...99,9 s. Reaching the preset limits is signalled by LED and simultaneously by the switch-on of the relevant relay.

DATA OUTPUTS are for their rate and accuracy suitable for transmission of the measured data for further projection or directly into the control systems. We offer an isolated RS232 and RS485 with the ASCII/PROFIBUS protocols.

ANALOG OUTPUTS will find their place in applications where further evaluating or processing of measured data is required in external devices. We offer universal analog output with the option of selection of the type of output - voltage/current. The value of analog output corresponds with the displayed data and its type and range are selectable in menu.

OM 352

OMLINK

The OM 352 model series are simple 3½-digit panel programmable instruments designed for maximum usefulness and user comfort while maintaining its fair price. Versions UNI, DC and AC are available.

Type OM 352UNI is a multifunction instrument with the option of configuration for 8 different input options, easily configurable in the instrument menu. Versions OM 352DC and OM 352AC are suitable for measurement of larger ranges of DC and AC voltages and currents.

The instrument is based on an 8-bit microcontroller and A/D converter, which ensures good accuracy, stability and easy operation of the instrument.

OM 352DC

DC VOLTMETER AND AMMETER

OM 352AC

AC VOLTMETER AND AMMETER

OM 352UNI

DC VOLTMETER AND AMMETER

PROCESS MONITOR

OHMMETER

THERMOMETER FOR Pt/Cu/Ni/Termocouples

DISPLAY UNIT FOR LINEAR POTENTIOMETERS

STANDARD FUNCTIONS

PROGRAMMABLE PROJECTION

Selection: of input type and measuring range

Setting (UNI): manual, in menu optional projection on the display may be set for both limit values of the input signal, e.g. input 0...19,99 V ⇒ 0...150,0

Projection: ±1999

COMPENSATION

Of conduct (RTD, OHM): automatic (3- and 4-wire) or manual in menu (2-wire)

of conduct in probe (RTD): internal connection (conduct resistance in measuring head)

of CJC (T/C): manual or automatic, in menu it is possible to perform selection of the type of thermocouple and compensation of cold junctions, which is adjustable or automatic (temperature at the input brackets)

LINEARIZATION

Linearization: through linear interpolation in 25 points (solely via OM Link)

DIGITAL FILTERS

Exponential average: from 2...100 measurements

Rounding: setting the projection step for display

FUNCTIONS

Tare: designed to reset display upon non-zero input signal

EXTERNAL CONTROL*

Hold: display/instrument blocking

Lock: control keys blocking

Tare: tare activation

TECHNICAL DATA

PROJECTION

Display: ±1999, red or green 7-segment LED, digit height 14 mm, -999...9999, red/green/orange 7-segment LED, digit height 20 mm
Decimal point: setting - in menu
Brightness: setting - in menu

INSTRUMENT ACCURACY

TK: 50 ppm/°C
Accuracy: ±0,2% of range + 1 digit (for projection ±1999) ±0,3% of range + 1 digit **AC, T/C**
Accuracy of cold junction measurement: ±1,5°C
Rate: 0,5...20 meas./s
Overload capacity: 10x [t < 30 ms] - not for > 200 V and 5 A; 2x
Resolution: 0,1°C [RTD], 1°C [T/C]
Watch-dog: reset after 500 ms
Functions: HOLD, LOCK, Digital filters, Tare
DM Link: Company communication interface for operation, setting and update of instruments
Calibration: at 25°C and 40 % r.h.

COMPARATOR

Type: digital, setting in menu, contact switch-on < 50 ms
Limits: ±1999; -999...9999
Hysteresis: 0...1999; -999...9999
Delay: 0...99,9 s
Output: 2x Form A relays [250 VAC/30 VDC, 3 A], 2x open collectors [30 VDC/100 mA]

DATA OUTPUT

Protocol: ASCII, PROFIBUS
Data format: 8 bit + no parity + 1 stop bit (ASCII)
Rate: 300...230 400 Baud
 9 600 Baud...12 Mbaud (PROFIBUS)
RS 232: isolated
RS 485: isolated, addressing (max. 31 instruments)

ANALOG OUTPUT

Type: isolated, programmable with resolution of max. 4 000 points, AD corresponds with the displayed data, type and range are selectable in programming mode
Non-linearity: 0,2% of range
TK: 100 ppm/°C
Rate: response to change of value < 250 ms
Ranges: 0...2/5/10 V, 0/4...20 mA [comp. < 500 Ω/12 V]

EXCITATION

Adjustable: 5...24 VDC/max. 1,2 W

POWER SUPPLY

10...30 V AC/DC, ±10 %, max. 13,5 VA, PF≥0,4, I_{50%}< 40 A/1 ms
 80...250 V AC/DC, ±10 %, max. 13,5 VA, PF≥0,4, I_{50%}< 40 A/1 ms
Power supply is protected by a fuse inside the instrument

MECHANICAL PROPERTIES

Material: Noryl GFN2 SE1, incombustible UL 94 V-1
Dimensions: 96 x 48 x 120 mm
Panel cutout: 90,5 x 45 mm

OPERATING CONDITIONS

Connection: connector terminal board, section < 1,5/2,5 mm²
Stabilization period: within 15 minutes after switch-on
Working temperature: -20°...60°C
Storage temperature: -20°...85°C
Cover: IP64 (front panel only)
El. safety: EN 61010-1, A2
Dielectric strength: 4 kVAC after 1 min between supply and input 4 kVAC after 1 min between supply and data/analog output 4 kVAC after 1 min between supply and relay output 2,5 kVAC after 1 min between input and data/analog output
Insulation resistance: for pollution degree II, measuring cat. III. Power supply > 670 V [ZI], 300 V [DI] input, output, Exc. > 300 V [ZI], 150 V [DI]
EMC: EN 61326-1

PI - Primary insulation, DI - Double insulation

MEASURING RANGES

DM 352 is a multifunction instrument available in following types and ranges

type UNI

DC: ±20/±60 mV/±1 V
PM: 0...20 mA/4...20 mA/0...2 V/5 V/10 V
OHM: 0...300 Ω/0...1,5 kΩ/0...3 kΩ/0...30 kΩ
RTD: Pt 50/100/Pt 500/Pt 1 000
Cu: Cu 50/Cu 100
Ni: Ni 1 000/Ni 10 000
T/C: J/K/T/E/B/S/R/N/L
DU: Linear potentiometer (min. 500 Ω)

type DC

DC - Hi: ±1 A/±5 A/±20 V/±40 V/±80 V/±200 V

type AC

AC: 0...1 A/0...5 A
 0...60 mV/0...300 mV/0...24 V/0...50 V/0...120 V/0...250 V/0...450 V

CONNECTING INDIVIDUAL INPUTS


	INPUT 1	INPUT 2	INPUT 3	INPUT 4	INPUT 5
DC	0...1 V		0...60 mV	0...20 mV	
PM	0...5/10 V				0...20 mA, 4...20 mA
T/C			J, K, E, N, L	B, S, R, T	
DC/Hi	±100/±200 V	±20/±40 V			±1/±5 A
AC	0...90/450 V	0...50/250 V	0...24/120 V	0...60/300 mV	0...0,5/1/5 A

SPECIFICATION OF INPUT RANGE IN THE ORDER CODE

UNI	
A	Pt 100/0...300 Ω
B	Pt 500/0...1 500 Ω
C	Pt 1 000/Ni 1 000/0...3 kΩ
D	Ni 10 000/0...30 kΩ
Z	on request

Only resistance type input ranges need to be specified at the point of order [OHM, RTD, Ni], other ranges [DC, PM, T/C, DU] are user selectable in the instrument's menu.

CONNECTION



ORDER CODE

OM 352

Type	U	N	I	D	C	A	C
Power supply	10...30 V AC/DC	80...250 V AC/DC	0	1			
Measuring ranges, see table "Specification"					?		
Comparators	no	1x relay (Form A)	2x relays (Form A)	1x open collector	2x open collectors	0	1 2 3 4
Output	none	Excitation	Analog output	RS 232	RS 485	PROFIBUS*	0 1 2 3 4 7
Display color	red (14 mm)	green (14 mm)	red/green (20 mm)				1 2 3
Other	customer version, do not fill in						00

*In the „UNI“ type the measuring range is selected under the order code solely for RTD, Ni, OHM. For other types this item has no significance with default setting „A“ !

Default execution is shown in bold

* Launch for sale has not been set